



With Viton seal, Ryton vane, PP spout and suction tube. Outlet can be freely rotated from 0° to 360°
Applicable Liquids: Acid alkali, alcohol, diesel fuel, gasoline, machine oil, water.
PATENTED IN TAIWAN, USA, CHINA, FRANCE.

- Pump Type: Rotary - Vane
 - Flow: 300 ml / Rotation
 - Maximum Fluid Temperature: 130°F / 54°C
 - Mounting: 2" MNPT Bung Adapter
 - Suction Tube Length: 40" Maximum
 - Inlet: 1-1/4" O.D.
 - Outlet: 1" O.D. Curved Spout
 - Wetted Parts: Polypropylene,
 - Maximum Viscosity: 2,000 SSU
 - Option: Polyethylene Extension Hose
- Standard Packing: 6pcs/ctn, NW: 13.5kgs, GW: 14.5kgs, Cuft: 2.2'

Made from light weight, rust resistance and good abrasion resistance materials.

- Ideal for transferring many organic acids, organic alcohols, detergents, and other water soluble inorganic chemicals which are compatible with pump component materials.

Also suitable for transferring Lubricants based fluids, Cleaning Solutions, Anti-Freeze, Soaps, Edible Liquids, etc.

Ideal for heavy-duty use in industrial, automotive and agricultural applications.

- Supply with 2" bung adapter and a 3-piece PP suction tube to fit most 15, 30 and 55 gallon drums. Self-priming unit, dispenses approximately 300 ml per stroke.